

# PREMIER® Enclosed-Flame Direct-Fired Portable Heaters



## Enclosed flame design invented by L.B. White

Direct-fired efficiency with added safety

- ✓ **Enclosed flame** promotes safer work environments and provides option to duct
- ✓ **99% direct-fired fuel efficiency** boosted by remote thermostat and option to move air only like a fan
- ✓ **Quiet** with less than 70 dB operation
- Dual Fuel (DF) models quickly switch from NG to LP
- Fits through standard 36" door frame while handles and wheels on larger models provide maneuverability

### MODELS AVAILABLE IN:

LP      DF (LP/NG)



PREMIER®	40	80, 2.0	80 DF, 2.0	170, 2.0	170 DF, 2.0	350 DF, 2.0
BTU/HR rating	40,000	80,000	80,000	170,000	170,000	350,000
Heated air output (CFM)	330	450	450	1,200	1,200	2,500
Fuel type	LP	LP	LP, NG	LP	LP, NG	LP, NG
Fuel consumption LP gas max (lbs/hr)	1.9	3.7	3.7	7.9	7.9	16.2
Fuel consumption NG gas max (cu ft/hr)	-	-	80	-	170	350
Amps (start/continuous)	2.6 / 1.0	5.0 / 1.5	5.0 / 1.5	7.3 / 5.0	7.3 / 5.0	25.0* / 9.0
Motor horsepower	1/12	1/8	1/8	1/3	1/3	1
Running decibels	62	70	70	70	70	72
Unit length (in)	24.8	28	28	32.3	32.3	48.3
Unit width (in)	14.5**	13.5	13.5	24.3	24.3	28.0
Unit height (in)	16.3	22.0	22.0	32.0	32.0	41.0
Shipping weight (lb)	60.0	79.0	79.0	161.0	161.0	320.0
Case material	Tri-Shield****	Tri-Shield****	Tri-Shield****	Tri-Shield****	Tri-Shield****	Tri-Shield****
Electrical connection	Mounted inlet	Mounted inlet	Mounted inlet	Mounted inlet	Mounted inlet	Mounted inlet
Thermostat connection	Mounted inlet	Mounted inlet	Mounted inlet	Mounted inlet	Mounted inlet	Mounted inlet
Wheels	-	-	-	Semi-pneumatic	Semi-pneumatic	Semi-pneumatic
Ventilation (fan only)	S	S	S	S	S	S
Gas hose, regulator & thermostat	S	S	S	S	S	S
Outlet duct diameter (in)	8	12	12	12	12	18
Outlet duct max length (ft)	12	12	12	12	12	25
LINK™ ready	-	-	-	-	-	S
Certified to ANSI/CSA standards	U.S. & CA	U.S. & CA	U.S. & CA	U.S. & CA	U.S. & CA	U.S. & CA

S=Standard O=Optional

\* Amps spike over 15 during initial start-up. Check breaker capability.

\*\* 18.1 with optional thermostat bracket installed.

\*\*\* Tri-shield coated steel with three unique protective layers including: a non-corrosive hot-dipped, galvanized steel, an oven-cured epoxy primer and baked, thermosetting polyester.

### Accessories (sold separately):

- Duct, 8" x 12', Premier 40 w/ Duct Adapter, 132544
- Duct, 12" x 12', Premier 80/170 w/ Duct Adapter, 26346
- Duct, 18" x 12', Premier 350 w/ Duct Adapter, 22835

**L.B. WHITE LINK**  
L.B. White LINK™  
Now telematics-enabled to put critical alerts, runtime, location, and more at your fingertips.  
Learn more at [LBWhite.com/LINK](http://LBWhite.com/LINK).

**MADE IN USA**  
OF U.S. & IMPORTED PARTS

**CA RESIDENTS:**  
 **WARNING**  
Cancer and reproductive harm. See [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).