

NEW & ENHANCED

PREMIER® 350 DF 2.0

Enclosed Flame Portable Heater

PREMIER®	350 DF 2.0
BTU/H RATING	350,000
HEATED AIR OUTPUT (CFM)	2,500
FUEL TYPE	LP, NG
FUEL CONSUMPTION LP GAS MAX (LBS./HR.)	16.2
FUEL CONSUMPTION NAT. GAS MAX (CU.FT./HR.)	350
AMPS (STARTING/CONTINUOUS OPERATION)	25.0 / 9.0
AMPS (STANDARD 15 AMP CIRCUIT)	YES*
ELECTRICAL CONNECTION MOUNTED INLET	YES
MOTOR HORSEPOWER	1
RUNNING DECIBELS	72
LENGTH (IN.)	48.3
WIDTH (IN.)	28.0
HEIGHT (IN.)	41.0
SHIPPING WEIGHT (LBS.)	320.0
FAN ONLY MODE	S
TRI-SHIELD COATED CASE**	S
WHEELS	S
GAS PRESSURE REGULATOR (W/POL)	S
THERMOSTAT CONNECTION MOUNTED INLET	YES
THERMOSTAT (WEATHERPROOF W/ 1.4' CORD)	S
GAS HOSE	15'
DUCTING (W/ MAGNETIC DUCT ADAPTER)***	18" DIA. X 12" LONG-24442
LINK™ READY	S
CERTIFIED TO ANSI/CSA STANDARDS	YES

TWO YEAR WARRANTY



S=Standard

*Amps spike over 15 during initial start-up. Check breaker capability

** Tri-shield coating consists of 3 unique protective layers including: a non-corrosive hot-dipped galvanized steel, an oven-cured epoxy primer and baked, thermosetting polyester.

*** Ducts are optional. Part numbers listed. Duct part numbers can differ for previously built models. Please call L.B. White for specific part numbers.

CA RESIDENTS:



Cancer and reproductive harm. See www.P65Warnings.ca.gov.

Heaters ship standard to run at 0-2000 feet. To operate at higher altitudes, please note in order process to allow for appropriate deviation.

INNOVATIVE HEATING SOLUTIONS

411 Mason Street, Onalaska, WI 54650
(800) 345 7200
(608) 783 5691
(608) 783 6115, fax
www.lbwhite.com
Revised: 7/14/2021

MADE IN USA
OF U.S. & IMPORTED PARTS

© 2021 L.B. White Co.
All rights reserved.
All specifications are subject
to change without notice.